

ORIGINAL FEEDING DEVICE HAVING  
ORIGINAL SIZE INDICATOR

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to an original feeding device, which comprises a width direction aligning plate for an original having a predetermined size, and disposes an original size indicator for  
10 indicating an original size by aligning it with the width thereof.

Related Background Art

In a conventional original feeding device, in the event that an original is loaded, an original  
15 size is indicated by aligning a width direction aligning plate with an original size indicator provided on an original loading tray or sheet stack tray. Although the width direction aligning plate can easily and accurately decide its position by a  
20 size indicator for a user's eye looking down at the device, for example, it is not possible to check the original size indicator on the original loading tray upper surface from a low view point such as a posture of sitting on a wheelchair and the like, and it is  
25 difficult to decide the position of the width direction aligning plate.

Hence, the invention disclosed in Japanese

Patent Application Laid-Open No. 6-144594, provides a device in which a size indicator needle moves according to the movement of the width direction aligning plate, and by indicating the original size  
5 indicator provided on the elevation portion of the original feeding device, the size of the sheet loaded on the original loading tray can be checked even from a low view point.

However, in the invention disclosed in Japanese  
10 Patent Application Laid-Open No. 6-144594, there has been a problem in that, though the original size indicator is provided on the elevation portion of the original feeding device so that the sheet size can be checked from the low view point, the view point from  
15 an upper part than the original feeding device is unable to check the sheet size and thus an accurate positioning of the width direction aligning plate cannot be attained. When a copying is started without the position accurately decided, there are  
20 sometimes the cases where the original is biased, and a trouble such as a jam, a damage of the original and the like occurs.

#### SUMMARY OF THE INVENTION

25 The present invention has been made in view of such problems, and the object of the invention is to provide an original feeding device, which can easily

check a size of an original loaded on an original loading tray for a user of a high view point as well as a low view point for the original feeding device.

In order to achieve the object, the present  
5 invention provides an original feeding device characterized by the following constitution;

an original feeding device for feeding an original in the shape of a sheet, comprising:

a loading tray for loading the original;  
10 an indicator member having a scale for indicating an original size; and

an aligning member for aligning a width direction of the original loaded on the loading tray, and indicating the scale on the indicator member,

15 wherein the indicator member is disposed such that the original size indicated by the aligning member can be checked from any of a first view point from above for the original feeding device and a second view point having an equal height to the  
20 original feeding device and also sidelongly fronting the same device.

The above and other objects, features, and advantages of the invention will become apparent from the following detailed description taken in  
25 conjunction with the accompanying drawings.

# BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a whole view of an original feeding device pertaining to a first embodiment;

FIG. 2 is an enlarged view of a width direction  
5 aligning plate and its vicinity of the original feeding device pertaining to the first embodiment;

FIG. 3 is a view seen from above of original size indicator vicinity pertaining to the first embodiment;

10 FIG. 4 is a view seen from the sidelong front for the original feeding device pertaining to the first embodiment;

FIG. 5 is a view seen from the full front for the original feeding device pertaining to the first  
15 embodiment;

FIG. 6 is a whole view of the original feeding device pertaining to a second embodiment;

FIG. 7 is an enlarged view of the width direction aligning plate and its vicinity of the  
20 original feeding device pertaining to a second embodiment;

FIG. 8 is a view seen from above of the original size indicator vicinity pertaining to the second embodiment;

25 FIG. 9 is a view seen from the sidelong front for the original feeding device pertaining to the second embodiment;

FIG. 10 is a view seen from the full front for the original feeding device pertaining to the second embodiment;

FIG. 11 is a whole view of the original feeding  
5 device pertaining to a third embodiment;

FIG. 12 is an enlarged view of the width direction aligning plate and its vicinity of the original feeding device pertaining to the third embodiment;

10 FIG. 13 is a view seen from above of the original size indicator vicinity pertaining to the third embodiment;

FIG. 14 is a view seen from the sidelong front for the original feeding device pertaining to the  
15 third embodiment;

FIG. 15 is a view directly seen from the full front for the original feeding device pertaining to the third embodiment;

FIG. 16 is an enlarged view of the width  
20 direction aligning plate of the original feeding device and its vicinity pertaining to a fourth embodiment; and

FIG. 17 is a view seen from above of the original size indicator vicinity pertaining to the  
25 fourth embodiment.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will be described below based on the embodiments shown in the drawings.

(First Embodiment)

5           FIG. 1 is the whole view of an original feeding device 100 pertaining to a first embodiment. The original feeding device 100 shown in FIG. 1 is a publicly known device, comprising an original loading tray 2, a pair of width direction aligning plates 5  
10   and 6 mounted thereon, and an original discharge tray 3, wherein the original loaded on the original loading tray 2 is conveyed in order from above and is discharged to the original discharge tray 3.

          A device upper portion cover 1 is a cover of an  
15   original feeding device conveying portion, in which an original set LED 4 is disposed at an angular portion.

          The original set LED 4 is an LED for advising a user that the original is accurately loaded on the  
20   original loading tray when the original is placed there and the original is detected. If the original is accurately loaded, the original set LED is turned ON. By disposing the original set LED 4 on the angular portion made by the upper surface and the  
25   side surface of the device cover 1, a light-on of the LED 4 is allowed to be checked not only from the view point from above, but also from the low view point

from the side.

The original loaded on the original loading tray 2 is loaded on the center by the width direction aligning plates 5 and 6. The width direction aligning plate is made a pair by a rear member 5 and a front member 6, and depending on the original size, the position thereof is changed. Hence, when slid left and right, the width direction aligning plate is allowed to provide a feeling of clicking so that the width direction aligning plate is stopped at a predetermined position of the original size.

FIG. 2 is an enlarged view of the width direction aligning plate 6 and its vicinity. Since the width direction aligning plates 5 and 6 change their positions according to the original size when the original is loaded, they slide left and right. The width direction aligning plate 6 of the foreground side is made as low as possible in height so that a height as an original conveying guide and a visibility at a case of visual line being directed from a low position are compatible. An original size indicator 7 for aligning the position of the width direction aligning plate with the predetermined original size is disposed in an L letter shape from the device cover 1 upper surface to the side surface.

A top end of the width direction aligning plate is sharp, and is so shaped as to point to the

original size indicator 7 from an oblique or sidelong direction, so that the top end of the width direction aligning plate points to the original size indicator 7 on the device upper cover 1 upper surface in case  
5 of the first view point from above for the device, and points to the original size indicator 7 on the cover side surface in case of the second view point having a substantially equal height to the device and also obliquely or sidelongly fronting the device.

10        FIG. 3 is a view seen from above of the original size indicator 7 vicinity. In the even that the original is loaded, in case of the view point from above the device, the top end of the width direction aligning plate 6 is allowed to point to one  
15 point on the upper surface side of the original size indicator 7 disposed in the L-letter shape on the side surface from the device upper portion cover 1 upper surface. By aligning the top end of the width direction aligning plate 6 with the original  
20 indicator, the width direction aligning plate 6 can be easily operated from the view point from above. The top end of the width direction aligning plate 6 is sharp, and is shaped so as to point to the original size indicator 7 from an oblique direction.  
25 Note that the L-letter shaped original size indicator 7 may be disposed by being divided into two that are for use of the view point from above and the view



point from the side, respectively.

FIG. 4 is a view seen from the view point having a substantially equal height to the device and also obliquely or sidelongly fronting the device, and  
5 FIG. 5 is a view seen from the full (or direct) front for the device. In case of the view point from the full front, as shown in FIG. 5, with respect to the width direction aligning plate 6, only the side surface can be seen, but, as can be understood from  
10 FIG. 4, when the end portion of the width direction aligning plate 6 is slanted, and the point where two angular portions on the surface are joined together is aligned with the original size indicator 7 of the device upper portion cover 1 side surface, then the  
15 position of the width direction aligning plate 6 can be decided by the same original size indicator as the view point from above and also by the same point, thereby making the operation easily.

(Second Embodiment)

20 FIG. 6 is a whole view of an original feeding device 100 pertaining to a second embodiment, and FIG. 7 is an enlarged view of a width direction aligning plate 6 and its vicinity.

An original size indicator 7 is disposed in the  
25 L-letter shape on the side surface from a device upper portion cover 1 upper surface, and a triangular spot-faced arrow 20 showing the original size

indicator 7 when viewed from the upper side, on the cover surface is disposed on the upper surface of the width direction aligning plate 6.

FIG. 8 is a view seen from above of the original size indicator 7 vicinity. In case of the view point from above the device, the triangular spot-faced arrow 20 disposed on the upper surface of the width direction aligning plate 6 is aligned with the original size indicator 7 of the device upper cover 1 upper surface side, so that it is possible to easily align the position of the width direction aligning plate 6 with the predetermined original size.

FIG. 9 is a view seen from the view point having a substantially equal height to the device and also obliquely or substantially fronting the device, and FIG. 10 is a view seen from the full (or direct) front for the device. In case of the view point from the full front, as shown in FIG. 10, with respect to the width direction aligning plate 6, only the side surface can be seen, but, in case of the view point from the sidelong or oblique front, as shown in Fig. 9, the point where two angular portions of the trapezoid shaped width direction aligning plate 6 are aligned is aligned with the original size indicator 7, as in the case where viewed from the upper side, so that the position of the width direction aligning plate 6 can be aligned with the predetermined

original size. In this way, from both view points from above and the side also, the position can be aligned with the same point of the same original size indicator 7.

5           Note that, as with the first embodiment, even in the case where the L-letter shaped original size indicator 7 is divided into two that are for the upper surface and the side surface, respectively, the position of the width direction aligning plate 6 can  
10 be aligned by respective original size indicators.  
(Third Embodiment)

FIG. 11 is a whole view of an original feeding device 100 pertaining to a third embodiment, and FIG. 12 is an enlarged view of a width direction aligning  
15 plate 6 and its vicinity.

An original size indicator 10 is disposed on an original loading tray 2, and a protruded shape 8 showing the original size indicator 10 is disposed at the rear end of the width direction aligning plate 6.  
20 The original size indicator 7 is disposed on the device upper portion cover 1 side surface, and a protruded shape 9 showing the original size indicator 7 is provided on the tope end of the width direction aligning plate 6.

25           FIG. 13 is a view seen from above of original size indicator 10 vicinity. In case of a view point from above the device, the protruded shape 8 disposed

at the rear end of the width direction aligning plate 6 is aligned with the original size indicator 10 on the original loading tray 2, so that the position of the width direction aligning plate 6 can be easily  
5 aligned with the predetermined original size.

FIG. 14 is a view seen from the view point having a substantially equal height to the device and also obliquely or sidelongly fronting the device, and FIG. 15 is a view seen from the full (or direct)  
10 front for the device. In case of the view point from the full front, as shown in FIG. 15, with respect to the width direction aligning plate 6, only the side surface can be seen, but, in case of the view point from the sidelong or oblique front, as shown in FIG.  
15 14, the protruded shape 9 of the top end of the width direction aligning plate 6 is aligned with the original size indicator 7 of the device cover 1 side surface, so that the position of the width direction aligning plate 6 can be aligned with the  
20 predetermined original size.

Two separate original size indicators seen from above and from the sidelong or oblique front are provided, and each indicator points to separate portions, so that the position of the width direction  
25 aligning plate 6 can be easily aligned from two view points from above and from the sidelong or oblique front.

(Fourth Embodiment)

FIG. 16 is an enlarged view of a width  
direction aligning plate and its vicinity of an  
original feeding device 100 pertaining to a fourth  
5 embodiment, and FIG. 17 is a view seen from above of  
an original size indicator vicinity.

The fourth embodiment is different from the  
third embodiment in that a protruded shape 8 showing  
an original size indicator 10 is disposed at the rear  
10 end of a width direction aligning plate 5 at the rear  
side of the device. The original size indicator 7 is,  
as with the third embodiment, disposed at a device  
upper portion cover 1 upper portion, and a protruded  
shape 9 showing the original size indicator 7 is  
15 provided at the top end of a width direction aligning  
plate 6 of at the front side of the device.

In case of a view point from above the device,  
as shown in FIG. 17, the protruded shape 8 disposed  
at the top end of the rear width direction aligning  
20 plate 5 is aligned with an original size indicator 10  
on an original loading tray 2, so that the position  
of the width direction aligning plate 5 can be easily  
aligned with the predetermined original size.

Further, in case of the view point having a  
25 substantially equal height to the device and also  
obliquely or sidelongly fronting the device, as shown  
in FIG. 16, the protruded shape 9 disposed at the top

end of the front width direction aligning plate 6 is aligned with the original size indicator 7 of the device cover 1 side surface, so that the position of the width direction aligning plate 6 can be aligned  
5 with the predetermined original size.

Two separate original size indicators seen from above and from the sidelong or oblique front are provided, and each indicator points to separate portions so that the positions of the width direction  
10 aligning plates 5 and 6 can be easily aligned from two view points from above and from the sidelong or oblique front.